

# Loci

## Mobius36 Pendant System



### Color



Black



White

### North America

<b>Lamping</b>	0.4W integrated LED (replaceable)
<b>Driver</b>	Input voltage 120-277V Integral class 2 power supply TRIAC/ELV/0-10V dimming
<b>Color temperature</b>	2700K
<b>Cord</b>	Black TPE sheathed 3 conductor White TPE sheathed 3 conductor
<b>Canopy</b>	Black powder coated, Ø 23, H 2 (in) White powder coated, Ø 23, H 2 (in)
<b>Material</b>	Powder coated aluminum Acrylic diffuser
<b>Size</b>	L 23, W 23, H 48 (in)
<b>Weight</b>	45 LBS
<b>Country of origin</b>	United States
<b>Certification</b>	A small rectangular logo with the UL symbol and the word "CERTIFIED" below it.

Dry locations only. Clean with a dry duster or compressed air.

**Designed in Seattle, Washington, USA.**

Custom cords and canopies are available. Contact our offices for more information.

# Loci

Mobius36 Pendant System



## SPECIFICATION CODE

Example: QTY 1 LOCI-MO-36-R24-CU-48-SM-BP-BC

Qty. LOCI - MO - 36 - R24 - CU - 48 - SM - BP

1      2      3      4

For each number, make one selection and enter into the corresponding box above. \*Indicates modification with additional lead time and/or costs

DROP LENGTH	1	CANOPY MOUNTING		2
48	48" (standard)	SM		Surface mounted
60	60"	SP		Suspended
72	72"			
84	84"			

  

CANOPY POWDER COAT	3	CABLE COLOR		4
BP	Black	BC		Black
WP	White	WC		White
CP	Custom			

\*Drop length measured from top of canopy to bottom of lowest pendant.